

PA720

Class G Power Amplifier

ARCAM



Features

- 7 Channel Power Amplifier
- 7 x 140W Class G amplification (all channels driven)
- Class G amplification with 20W of Class A operation
- Toroidal transformer
- Ethernet, RS232 control
- Switchable RCA or balanced XLR inputs

Exceptional Power, Immersive Sound

The PA720 is a high-performance power amplifier that delivers 7 channels of efficient Class G amplification. With an impressive 140W per channel, the PA720 is designed to offer the greatest flexibility and power without compromising on control.

Featuring the best-in-class components including a toroidal based power supply, acoustically damped chassis, paralleled transistor output stages and exceptionally low levels of distortion, the PA720 masters the reproduction of music with all its originality and detail for an unmatched level of sound quality and clarity.

PA720

Class G Power Amplifier

ARCAM

Continuous power output at 0.2% THD per channel

Seven channels driven, 4Ω / 8Ω, 20Hz – 20kHz	140W / 100W
Five channels driven, 4Ω / 8Ω, 1kHz	175W / 110W
Two channels driven, 4Ω / 8Ω, 1kHz	225W / 140W
Harmonic distortion, 80% power, 8Ω at 1kHz	0.002%

Inputs

	RCA Type	XLR Type
Input sensitivity 50W / 8Ω	800mV RMS	1.6V RMS
Signal/Noise ratio (A-wtd) 50W / 8Ω	105dB	
Input impedance	10kΩ	
Frequency response	20 - 20kHz +/-0.05dB	

General

Mains voltage	110–120V or 220–240V, 50–60Hz
Power consumption (maximum)	1.5kW
Power consumption (idle, typical)	90W (Thermal dissipation approx. 340 BTU/hour)
Power consumption (standby)	<0.5W
Dimensions W x H x D (including feet, control knob and speaker terminals)	433 x 425 x 177mm
Weight (net)	18kg
Weight (packed)	19.7kg
EAN	625281956720

